

# CYLINDERS

Continued  
3 - 1 - 10

DEAN BENNETT SUPPLY CO.  
Toll Free : 800-621-4291  
PRICES ARE YOUR NET COSTS  
Page 61a

## # 652-B STEEL CASE / BRASS LINED DEEP WELL CYLINDERS

These #652-B cylinders are heavy duty and designed for your deepest well settings. Made with seamless brass tube that lines a standard Schedule 40 galvanized steel pipe. These open top cylinders come with 4-leather ball valve plunger assemblies and ball valve bottom check valves. Plungers are tapped so that they can screw onto the bottom check valve for easy removal from the well without having to pull the drop pipe. We stock these in a 48" long barrel design for strokes up to 36" or to allow for two settings of stroke in the same tubing length.



**\$ 381.00**    **1-7/8" x 36" x 48"**    2" male iron pipe thread on top ( you will need a 2" pipe coupling )  
652B178            Plunger tapped for 5/8" rod thread    48" overall length of cylinder allows up to a 36" stroke  
Comes complete with 4-leather ball valve plunger and ball valve bottom check valve  
( replacement #652 plunger assembly \$ 125.00    replacement #652 bottom check valve assembly  
\$ 71.50 ) Weight 26 lbs

**\$ 502.00**    **2-1/4" x 36" x 48"**    2-1/2" male iron pipe thread on top ( you need a 2-1/2" pipe coupling )  
652B214            Plunger tapped for 7/8" rod thread    48" overall length of cylinder allows up to 36" stroke  
( replacement #652 plunger assembly \$ 165.00    replacement #652 bottom check valve assembly  
\$ 102.00 ) Weight 36 lbs

**\$ 718.00**    **2-3/4" x 32" x 48"**    3" male iron pipe thread on top ( you need a 3" pipe coupling ) Plunger  
652B234            tapped for 7/8" rod thread    48" overall length of cylinder allows up to 32" stroke    ( replacement  
#652 plunger assembly \$ 229.00    replacement #652 bottom check valve assembly \$ 162.00 )  
Weight 55 lbs

## ALL BRASS SLIM-LINE CYLINDERS TO ENTER 2" SCH 40 PIPE

These two sizes of #442 Flush Cap Cylinders will enter 2" Sch 40 drop pipe. If your pipe is old and possibly corroded or if your 2" drop pipe might be crooked, you should use the smaller 1-11/16" size, as the additional 1/8" may make the difference between being able to install your cylinder or having it hang up in your well.

**\$ 155.00**    **1-11/16" x 10" x 18"**    #442 All Brass Flush Cap Cylinder    7/16" rod connection  
44211116            for 1" drop pipe connection    up to 10" stroke.

**\$ 135.00**    **1-13/16" x 10" x 18"** #442 All Brass Flush Cap Cylinder    7/16" rod connection  
44211316            for 1" drop pipe connection    up to 10" stroke.

## 1-3/16" COLD STEEL SINKER BARS TO ENHANCE CYLINDER EFFICIENCY

Sinker Bars are used with sucker rod strings that are non-rigid or that are lighter than 43 lbs per 100 ft. These steel sinker bars when connected to the working plunger assembly in the cylinder may increase pumping capacity by up to 30%, by keeping tension on the rod string and helping insure the full stroke of the cylinder. A sinker bar that has been precision machined will also help insure the proper alignment of the working plunger in the cylinder, thus increasing the efficiency and expected life of the cylinder. Sinker bars should be a minimum of 10 lbs, or 1 lb for each 23' of rod, whichever is greater. You can use additional sinker bars in your installation to gain additional weight if required by the deeper settings of your rod string. These sinker bars are painted to resist corrosion.

These 1045 cold steel sinker bars are 31" long and weigh 10 lbs each.

<b>\$ 79.95</b>	<b>#370570</b>	<b>31" Sinker Bar</b>	<b>Threaded 5/8" male x 5/8" female</b>
<b>\$ 79.95</b>	<b>#370575</b>	<b>31" Sinker Bar</b>	<b>Threaded 7/8" male x 5/8" female</b>
<b>\$ 79.95</b>	<b>#370580</b>	<b>31" Sinker Bar</b>	<b>Threaded 5/8" male x 7/8" female</b>
<b>\$ 79.95</b>	<b>#370585</b>	<b>31" Sinker Bar</b>	<b>Threaded 7/8" male x 7/8" female</b>

YOU CAN COMBINE WELL CYLINDERS WITH OTHER ITEMS IN OUR CATALOG  
TO QUALIFY FOR OUR \$ 1000.00 FULL FREIGHT PREPAID ORDER POLICY.